

## Scheda Dati

010BA9SLR400  
Punainen multichip led-valo, BA9S, 400 V AC-DC, kiinteä valo



## Caratteristiche

|                  |                                                              |
|------------------|--------------------------------------------------------------|
| Range            | Led-lamput BA9S kiinteä valo                                 |
| Componente       | 400V AC-DC                                                   |
| Code             | 010BA9SLR400                                                 |
| Kuvaus           | Punainen multichip led-valo, BA9S, 400 V AC-DC, kiinteä valo |
| Väriä            | Rosso                                                        |
| Peso             | 2,0                                                          |
| Tariffa doganale | 8539520000                                                   |
| GT               | 8052878000660                                                |

## Dati tecnici

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| Approvals                          | CE                                                |
| Compliance with standards          | IEC-EN62471                                       |
| Compliance to EMC standards        | EN55015, EN61000-3-2, EN61000-3-3, EN61547        |
| Lighting type                      | LED bulb                                          |
| Bulb base                          | Ba9S bayonet (IEC-EN60061-1)                      |
| Signalling type                    | Steady                                            |
| Operating temperatures             | -25° ÷ +70°C                                      |
| Available models (ratings +/- 20%) | AC/DC 6V-7mA, 12V-8mA, 24V-7.5mA, 36V-7.5mA,      |
| Available models (ratings +/- 20%) | AC/DC 48V-5.5mA, 130V-3.2mA, 240V-2.5mA, 400V-1mA |
| Operating voltage tolerance        | Vn +10% / -20%                                    |
| Electrical life                    | 50.000h                                           |
| Warranty period                    | 18 months                                         |

Disegni tecnici

