

## Hoja de datos

010CSN12X05-3  
Cable enrollado



## Características

<b>Rango</b>	Cable enrollado para cajas botoneras
<b>Componente</b>	Cable enrollado
<b>Código</b>	010CSN12X05-3
<b>Descripción</b>	Cable enrollado
<b>Peso</b>	700,0
<b>Arancel aduanero</b>	85365080
<b>GTIN</b>	8052878067038

## Datos técnicos

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC 60228 class 6 - DIN47100
<b>Operating temperatures</b>	-5° ÷ +70°C
<b>Cross section</b>	12x0.5mm <sup>2</sup> - 12x20 AWG - unshielded
<b>Rated voltage</b>	500V
<b>Test voltage</b>	2000V
<b>External sheath</b>	PUR polyurethane - black - diameter 8.8mm
<b>Core insulation</b>	PVC / TPE
<b>Core number</b>	12
<b>Core identification (by colors)</b>	According to DIN 47100
<b>Bare copper-conductor</b>	IEC 60228 cl.6 / 0.5mm <sup>2</sup> (20 AWG)
<b>External / internal coils diameters</b>	40mm / 22mm
<b>Optimal working length</b>	1÷3m - max.extension 4.5m
<b>Warranty period</b>	18 months

## Dibujos técnicos

