

## Scheda Dati

016P3P33

Botão de habilitação, 3 posições, 3 N.O.+3 N.C, terminais T7 a soldar



## Caratteristiche

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| Gama             | Botões de habilitação de 3 posições Ø 16 mm                           |
| Componente       | Sem proteção, terminais T7 a soldar                                   |
| Código           | 016P3P33                                                              |
| Descrição        | Botão de habilitação, 3 posições, 3 N.O.+3 N.C, terminais T7 a soldar |
| Cor              | Nero                                                                  |
| Peso             | 31,0                                                                  |
| Tariffa doganale | 85365080                                                              |
| GTIN             | 8052878001872                                                         |

## Dati tecnici

|                                       |                                                   |
|---------------------------------------|---------------------------------------------------|
| Approvals                             | CE, (UL-CSA Microswitch only)                     |
| Compliance with standards             | IEC-EN60947-5-8, IEC-EN60204-1, IEC-EN11161       |
| Operating temperatures                | -30° ÷ +70°C                                      |
| Protection degree                     | IP40 - IP66 with 016GP28+020CGS (IEC-EN60529)     |
| Protection against impact             | IK06 (IEC-EN62262)                                |
| Mechanical durability                 | Position 1-2: 1.000.000 operations                |
| Mechanical durability                 | Position 2-3: 500.000 operations                  |
| Safety Parameters                     | B10d:1.000.000 oper. pos.2-3 (UNI-EN-ISO 13849-1) |
| Fixing diameter                       | 16.5mm - Thickness 1÷6mm                          |
| Tightening torque                     | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)                      |
| Rated insulation voltage              | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)              |
| Protection against electric shock     | Class I (IEC-EN61140)                             |
| Microswitches electrical ratings      | Vn 250V max AC-DC, In 5Amax, Ith 10A, Ui 300V     |
| Microswitches electrical performances | 20.000 operations with load 250V-5A-cosphi 0.8    |
| Actuating forces                      | Position 1-2: 10N Position 2-3: 25N               |
| Microswitch                           | 1NO - 1NC change over, snap action                |
| Warranty period                       | 18 months                                         |

Disegni tecnici

