

Fiche technique

016P3P33F

Poignée d'assentiment à 3 positions, 3 N.O.+3 N.C, cosses Faston 2.8x0.5



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Poignées d'assentiment à 3 positions Ø 16 mm |
| Composant | Sans garde avec control de posición, cosses faston |
| Code | 016P3P33F |
| Désignation des marchandises | Poignée d'assentiment à 3 positions, 3 N.O.+3 N.C, cosses Faston 2.8x0.5 |
| Couleur | Nero |
| Poids | 35,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878001889 |

Données techniques

| | |
|--|---|
| Approvals | CE, (UL-CSA Microswitch only) |
| Compliance with standards | IEC-EN60947-5-8, IEC-EN60204-1, IEC-EN11161 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP40 - IP66 with 016GP28+020CGS (IEC-EN60529) |
| Protection against impact | IK06 (IEC-EN62262) |
| Mechanical durability | Position 1-2: 1.000.000 operations |
| Mechanical durability | Position 2-3: 500.000 operations |
| Safety Parameters | B10d:1.000.000 oper. pos.2-3 (UNI-EN-ISO 13849-1) |
| Fixing diameter | 16.5mm - Thickness 1÷6mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Microswitches electrical ratings | Vn 250V max AC-DC, In 5Amax, Ith 10A, Ui 300V |
| Microswitches electrical performances | 20.000 operations with load 250V-5A-cosphi 0.8 |
| Actuating forces | Position 1-2: 10N Position 2-3: 25N |
| Microswitch | 1NO - 1NC change over, snap action |
| Warranty period | 18 months |

Dessins techniques

