

Hoja de datos

016P3PCG44

Pulsador de activación, 3 posiciones, capuchón de caucho 4 N.O.+4 N.C., terminales T7 a soldar



Características

| | |
|-------------------------|--|
| Rango | Pulsadores de activación de 3 posiciones Ø 16 mm |
| Componente | Capuchón de caucho transparente, terminales T7 a soldar |
| Código | 016P3PCG44 |
| Descripción | Pulsador de activación, 3 posiciones, capuchón de caucho 4 N.O.+4 N.C., terminales T7 a soldar |
| Color | Nero |
| Peso | 48,0 |
| Arancel aduanero | 85365080 |
| GTIN | 8052878065966 |

Datos técnicos

| | |
|--|---|
| Approvals | CE, (UL-CSA Microswitch only) |
| Compliance with standards | IEC-EN60947-5-8, IEC-EN60204-1, IEC-EN11161 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK06 (IEC-EN62262) |
| Mechanical durability | Position 1-2: 1.000.000 operations |
| Mechanical durability | Position 2-3: 500.000 operations |
| Safety Parameters | B10d:1.000.000 oper. pos.2-3 (UNI-EN-ISO 13849-1) |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Microswitches electrical ratings | Vn 250V max AC-DC, In 5Amax, Ith 10A, Ui 300V |
| Microswitches electrical performances | 20.000 operations with load 250V-5A-cosphi 0.8 |
| Actuating forces | Position 1-2: 10N Position 2-3: 25N |
| Microswitch | 1NO - 1NC change over, snap action |
| Warranty period | 18 months |

Dibujos técnicos

