

## Fiche technique

016P3PCG44

Poignée d'assentiment à 3 positions avec capuchón de caucho 4 N.O.+4 N.C, cosses T7 à souder



## Caractéristiques

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Poignées d'assentiment à 3 positions Ø 16 mm   |
| <b>Composant</b>                    | Capuchon en caoutchouc, cosses T7 à souder   |
| <b>Code</b>                         | 016P3PCG44   |
| <b>Désignation des marchandises</b> | Poignée d'assentiment à 3 positions avec capuchón de caucho 4 N.O.+4 N.C, cosses T7 à souder |
| <b>Couleur</b>                      | Nero   |
| <b>Poids</b>                        | 48,0   |
| <b>Tarif douanier</b>               | 85365080   |
| <b>GTIN</b>                         | 8052878065966  |

## Données techniques

|  |   |
|--|---|
| <b>Approvals</b>                             | CE, (UL-CSA Microswitch only)                     |
| <b>Compliance with standards</b>             | IEC-EN60947-5-8, IEC-EN60204-1, IEC-EN11161       |
| <b>Operating temperatures</b>                | -30° ÷ +70°C                                      |
| <b>Protection degree</b>                     | IP66 - IP69 (IEC-EN60529)                         |
| <b>Protection against impact</b>             | IK06 (IEC-EN62262)                                |
| <b>Mechanical durability</b>                 | Position 1-2: 1.000.000 operations                |
| <b>Mechanical durability</b>                 | Position 2-3: 500.000 operations                  |
| <b>Safety Parameters</b>                     | B10d:1.000.000 oper. pos.2-3 (UNI-EN-ISO 13849-1) |
| <b>Fixing diameter</b>                       | 22.5mm - Thickness 1÷6mm                          |
| <b>Tightening torque</b>                     | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                       |
| <b>Rated insulation voltage</b>              | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)              |
| <b>Protection against electric shock</b>     | Class I (IEC-EN61140)                             |
| <b>Microswitches electrical ratings</b>      | Vn 250V max AC-DC, In 5Amax, Ith 10A, Ui 300V     |
| <b>Microswitches electrical performances</b> | 20.000 operations with load 250V-5A-cosphi 0.8    |
| <b>Actuating forces</b>                      | Position 1-2: 10N Position 2-3: 25N               |
| <b>Microswitch</b>                           | 1NO - 1NC change over, snap action                |
| <b>Warranty period</b>                       | 18 months   |

# Dessins techniques

