

Datenblatt

016P3PG33

Freigabeschalter mit Frontring, 3 Positionen, 3NO+2NC T7 Lötanschlüsse



Merkmale

| | |
|------------------------|--|
| Baureihe | Freigabeschalter, 3 Positionen, Ø 16 mm |
| Komponenten | Mit Frontring mit Lageregelungf, T7 Lötanschlüsse |
| Artikel-Nr. | 016P3PG33 |
| Beschreibung | Freigabeschalter mit Frontring, 3 Positionen, 3NO+2NC T7 Lötanschlüsse |
| Farbe | Nero |
| Gewicht - gr | 44,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878065331 |

Technische Daten

| | |
|--|---|
| Approvals | CE, (UL-CSA Microswitch only) |
| Compliance with standards | IEC-EN60947-5-8, IEC-EN60204-1, IEC-EN11161 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP40 - IP66 with 016GP28+020CGS (IEC-EN60529) |
| Protection against impact | IK06 (IEC-EN62262) |
| Mechanical durability | Position 1-2: 1.000.000 operations |
| Mechanical durability | Position 2-3: 500.000 operations |
| Safety Parameters | B10d:1.000.000 oper. pos.2-3 (UNI-EN-ISO 13849-1) |
| Fixing diameter | 16.5mm - Thickness 1÷6mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Microswitches electrical ratings | Vn 250V max AC-DC, In 5Amax, Ith 10A, Ui 300V |
| Microswitches electrical performances | 20.000 operations with load 250V-5A-cosphi 0.8 |
| Actuating forces | Position 1-2: 10N Position 2-3: 25N |
| Microswitch | 1NO - 1NC change over, snap action |
| Warranty period | 18 months |

Technische Zeichnungen

