

Fiche technique

016P3PG33F

Poignée affleurants d'assentiment à 3 positions, 3NO+3NC cosses Faston 2.8x0.5



Caractéristiques

Portée	Poignées d'assentiment à 3 positions Ø 16 mm
Composant	Affleurant avec control de posición, cosses faston
Code	016P3PG33F
Désignation des marchandises	Poignée affleurants d'assentiment à 3 positions, 3NO+3NC cosses Faston 2.8x0.5
Couleur	Nero
Poids	46,0
Tarif douanier	85365080
GTIN	8052878065362

Données techniques

Approvals	CE, (UL-CSA Microswitch only)
Compliance with standards	IEC-EN60947-5-8, IEC-EN60204-1, IEC-EN11161
Operating temperatures	-30° ÷ +70°C
Protection degree	IP40 - IP66 with 016GP28+020CGS (IEC-EN60529)
Protection against impact	IK06 (IEC-EN62262)
Mechanical durability	Position 1-2: 1.000.000 operations
Mechanical durability	Position 2-3: 500.000 operations
Safety Parameters	B10d:1.000.000 oper. pos.2-3 (UNI-EN-ISO 13849-1)
Fixing diameter	16.5mm - Thickness 1÷6mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Microswitches electrical ratings	Vn 250V max AC-DC, In 5Amax, Ith 10A, Ui 300V
Microswitches electrical performances	20.000 operations with load 250V-5A-cosphi 0.8
Actuating forces	Position 1-2: 10N Position 2-3: 25N
Microswitch	1NO - 1NC change over, snap action
Warranty period	18 months

Dessins techniques

