

## Fiche technique

020LMAG

Voyant lumineux monolithique BA9S, H 30, jaune, alimentation directe



## Caractéristiques

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Voyants lumineux Ø 22  |
| <b>Composant</b>                    | Monolithiques BA9S, H 30   |
| <b>Code</b>                         | 020LMAG  |
| <b>Désignation des marchandises</b> | Voyant lumineux monolithique BA9S, H 30, jaune, alimentation directe |
| <b>Couleur</b>                      | Giallo   |
| <b>Poids</b>                        | 22,0   |
| <b>Tarif douanier</b>               | 85365080   |
| <b>GTIN</b>                         | 8052878004538  |

## Données techniques

|                                       |  |
|---------------------------------------|--|
| <b>Approvals</b>                      | CE, UL, CSA  |
| <b>Compliance with standards</b>      | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Compliance with standards</b>      | UNI CEI EN 45545-2, CEI EN 61373                   |
| <b>Operating temperatures</b>         | -40° ÷ +70°C                                       |
| <b>Environmental operating values</b> | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)       |
| <b>Protection degree</b>              | IP66 - IP69 (IEC-EN60529)                          |
| <b>Protection against impact</b>      | IK03 (IEC-EN62262)                                 |
| <b>Shock resistance</b>               | 30g duration=18ms (EN-IEC 60068-2-27)              |
| <b>Shock resistance</b>               | 50g duration=11ms (EN-IEC 60068-2-27)              |
| <b>Vibration resistance</b>           | 5g f= 2...500Hz (EN-IEC 60068-2-6)                 |
| <b>Material</b>                       | PA Polyamide                                       |
| <b>Lens material</b>                  | PC Polycarbonate                                   |
| <b>Locking ring material</b>          | PA Polyamide                                       |
| <b>Fixing diameter</b>                | 22.5mm - Thickness 1÷6mm                           |
| <b>Terminal screw</b>                 | Tightening torque 0.8÷1 Nm (IEC-EN60947-1)         |
| <b>Terminal screw head shape</b>      | Combined:cross Phillips2 or slotted flat D.5mm max |
| <b>Terminal screw material</b>        | Zinc plated steel                                  |
| <b>Tightening torque</b>              | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                         |
| <b>Bulb type</b>                      | Ba9S 400V - 2W max (not included)                  |
| <b>Rated insulation voltage</b>       | Ui 690V - Uimp 4KV (IEC-EN60947-1)                 |

---

**Protection against electric shock**

Class II (IEC-EN61140)

---

**Warranty period**

18 months

---

## Dessins techniques

