

## Scheda Dati

020LMB

Lâmpada indicador luminoso monobloco, BA9S, branca, alimentação direta



## Caratteristiche

|                  |                                                                        |
|------------------|------------------------------------------------------------------------|
| Gama             | Lâmpadas indicador luminoso Ø 22                                       |
| Componente       | Lâmpadas indicador luminoso monobloco BA9S                             |
| Código           | 020LMB                                                                 |
| Descrição        | Lâmpada indicador luminoso monobloco, BA9S, branca, alimentação direta |
| Cor              | Bianco                                                                 |
| Peso             | 18,0                                                                   |
| Tariffa doganale | 85365080                                                               |
| GTIN             | 8052878004576                                                          |

## Dati tecnici

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| Approvals                      | CE, UL, CSA                                        |
| Compliance with standards      | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Compliance with standards      | UNI CEI EN 45545-2, CEI EN 61373                   |
| Operating temperatures         | -40° ÷ +70°C                                       |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)       |
| Protection degree              | IP66 - IP69 (IEC-EN60529)                          |
| Protection against impact      | IK03 (IEC-EN62262)                                 |
| Shock resistance               | 30g duration=18ms (EN-IEC 60068-2-27)              |
| Shock resistance               | 50g duration=11ms (EN-IEC 60068-2-27)              |
| Vibration resistance           | 5g f= 2...500Hz (EN-IEC 60068-2-6)                 |
| Material                       | PA Polyamide                                       |
| Lens material                  | PC Polycarbonate                                   |
| Locking ring material          | PA Polyamide                                       |
| Fixing diameter                | 22.5mm - Thickness 1÷6mm                           |
| Terminal screw                 | Tightening torque 0.8÷1 Nm (IEC-EN60947-1)         |
| Terminal screw head shape      | Combined:cross Phillips2 or slotted flat D.5mm max |
| Terminal screw material        | Zinc plated steel                                  |
| Tightening torque              | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                         |
| Bulb type                      | Ba9S 400V - 2W max (not included)                  |
| Rated insulation voltage       | Ui 690V - Uimp 4KV (IEC-EN60947-1)                 |

|                                   |                        |
|-----------------------------------|------------------------|
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period                   | 18 months              |

Disegni tecnici

