

Scheda Dati

020LMI

Lâmpada indicador luminoso monobloco, BA9S, incolor, alimentação direta



Caratteristiche

Gama	Lâmpadas indicador luminoso Ø 22
Componente	Lâmpadas indicador luminoso monobloco BA9S
Código	020LMI
Descrição	Lâmpada indicador luminoso monobloco, BA9S, incolor, alimentação direta
Cor	Incolore
Peso	18,0
Tariffa doganale	85365080
GTIN	8052878004613

Dati tecnici

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	PA Polyamide
Fixing diameter	22.5mm - Thickness 1÷6mm
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined:cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Bulb type	Ba9S 400V - 2W max (not included)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)

Protection against electric shock

Class II (IEC-EN61140)

Warranty period

18 months

Disegni tecnici

