

Datasheet

020LTBBAW

Tamper-proof pilot light, convex lens, orange, metal



Features

| | |
|----------------|--|
| Range | Pilot lights Ø 22 - metal bezel |
| components | Tamper-proof |
| Code | 020LTBBAW |
| Description | Tamper-proof pilot light, convex lens, orange, metal |
| Colour | Arancio |
| Weight - gr | 30.0 |
| Customs Tariff | 85365080 |
| GTIN | 8052878064013 |

Datasheet

| | |
|-----------------------------------|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Material | PA Polyamide |
| External bezel material | Chromed zinc alloy |
| Lens material | PC Polycarbonate |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Front panel | Tamper proof lens |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Modular pilot light | Must be completed with bulb holder-power supply |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Technical drawings

