

Datasheet

020LTBBBW

Tamper-proof pilot light, convex lens, white, metal



Features

Range	Pilot lights Ø 22 - metal bezel
components	Tamper-proof
Code	020LTBBBW
Description	Tamper-proof pilot light, convex lens, white, metal
Colour	Bianco
Weight - gr	30.0
Customs Tariff	85365080
GTIN	8052878064037

Datasheet

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Material	PA Polyamide
External bezel material	Chromed zinc alloy
Lens material	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Front panel	Tamper proof lens
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Modular pilot light	Must be completed with bulb holder-power supply
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Technical drawings

