

Scheda Dati

020LTBBGW  
Lâmp.indic.lumin.inviol., gema abaulada, amarela, metal



Caratteristiche

|                  |                                                         |
|------------------|---------------------------------------------------------|
| Gama             | Lâmpadas indicador luminoso Ø 22 - anel em metal        |
| Componente       | Lâmpadas indicador luminoso invioláveis                 |
| Código           | 020LTBBGW                                               |
| Descrição        | Lâmp.indic.lumin.inviol., gema abaulada, amarela, metal |
| Cor              | Giallo                                                  |
| Peso             | 30,0                                                    |
| Tariffa doganale | 85365080                                                |
| GTIN             | 8052878064044                                           |

Dati tecnici

|                                   |                                                  |
|-----------------------------------|--------------------------------------------------|
| Approvals                         | CE                                               |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards         | UNI CEI EN 45545-2                               |
| Operating temperatures            | -25° ÷ +65°C                                     |
| Environmental operating values    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| Protection degree                 | IP65 (IEC-EN60529)                               |
| Protection against impact         | IK03 (IEC-EN62262)                               |
| Shock resistance                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Material                          | PA Polyamide                                     |
| External bezel material           | Chromed zinc alloy                               |
| Lens material                     | PC Polycarbonate                                 |
| Locking ring material             | Zamak zinc alloy                                 |
| Fixing diameter                   | 22.5mm - Thickness 1÷6mm                         |
| Front panel                       | Tamper proof lens                                |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Modular pilot light               | Must be completed with bulb holder-power supply  |
| Protection against electric shock | Class II (IEC-EN61140)                           |
| Warranty period                   | 18 months                                        |

## Disegni tecnici

