

Fiche technique

020MTR1T3P

Manipulateur, 4 positions, 3 Maintenues 1 Rappel à zéro, H 45




Caractéristiques

Portée	Manipulateurs Ø 22
Composant	4 positions H 45 mm
Code	020MTR1T3P
Désignation des marchandises	Manipulateur, 4 positions, 3 Maintenues 1 Rappel à zéro, H 45
Couleur	Grigio RAL7016
Poids	38,0
Tarif douanier	85365080
GTIN	8052878067236

Données techniques

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Material	PA Polyamide
Cap or bellow material	Silicon rubber
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Dessins techniques



020G
 020E01
 020E01
 020E10
 020E10