

## Scheda Dati

020MTR4T  
Manipulador, 4 posições, 4 temporárias, H 45








## Caratteristiche

|                  |                                              |
|------------------|----------------------------------------------|
| Gama             | Manipuladores Ø 22                           |
| Componente       | Manipuladores de 4 posições H 45 mm          |
| Código           | 020MTR4T                                     |
| Descrição        | Manipulador, 4 posições, 4 temporárias, H 45 |
| Cor              | Grigio RAL7016                               |
| Peso             | 38,0                                         |
| Tariffa doganale | 85365080                                     |
| GTIN             | 8052878004903                                |

## Dati tecnici

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| Approvals                      | CE, UL, CSA                                      |
| Compliance with standards      | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards      | UNI CEI EN 45545-2, CEI EN 61373                 |
| Operating temperatures         | -40° ÷ +70°C                                     |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| Protection degree              | IP66 - IP69 (IEC-EN60529)                        |
| Protection against impact      | IK03 (IEC-EN62262)                               |
| Mechanical durability          | 1.000.000 Operations                             |
| Shock resistance               | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance               | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance           | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Contact blocks configuration   | Max no. 4 blocks (2+2)                           |
| Material                       | PA Polyamide                                     |
| Cap or bellow material         | Silicon rubber                                   |
| Locking ring material          | Zamak zinc alloy                                 |
| Fixing diameter                | 22.5mm - Thickness 1÷6mm                         |
| Tightening torque              | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Warranty period                | 18 months                                        |

Disegni tecnici



020G  
020E01  
020E01  
020E10  
020E10

