

Datablad

020PLIGPP

Lichtdrukknop met bescherming, geel, Bescherming kleurloos vergrendeling, veer sluiting



Kenmerken

Bereik	Lichtdrukknoppen Ø 22
Component	Drukknoppen met bescherming, afsluitbare bescherming
Rubriek	020PLIGPP
Omschrijving	Lichtdrukknop met bescherming, geel, Bescherming kleurloos vergrendeling, veer sluiting
Kleur	Giallo
Gewicht	28,0
Douanetarief	85365080
GTIN	8052878074630

Technische gegevens

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	3.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 8 blocks (4+4)
Material	PA Polyamide
Button/mushroom material (illuminated type)	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Spring return
Protection against electric shock	Class II (IEC-EN61140)
Illuminated version	Use Ba9S bulbs with 24mm height max.

Warranty period

18 months

Technische tekeningen

