

## Scheda Dati

### 020PLPCGB

Painike täydellisellä suojuksella, valopainike, valkoinen, kumikorkki



## Caratteristiche

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| Range            | Valopainikkeet Ø 22                                                   |
| Componente       | Painike täydellisellä suojuksella ja korkilla                         |
| Code             | 020PLPCGB                                                             |
| Kuvaus           | Painike täydellisellä suojuksella, valopainike, valkoinen, kumikorkki |
| Väriä            | Bianco                                                                |
| Peso             | 23,0                                                                  |
| Tariffa doganale | 85365080                                                              |
| GT               | 8052878007003                                                         |

## Dati tecnici

|                                             |                                                  |
|---------------------------------------------|--------------------------------------------------|
| Approvals                                   | CE, UL, CSA                                      |
| Compliance with standards                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures                      | -40° ÷ +70°C                                     |
| Environmental operating values              | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| Protection degree                           | IP67 - IP69 (IEC-EN60529)                        |
| Protection against impact                   | IK04 (IEC-EN62262)                               |
| Mechanical durability                       | 3.000.000 Operations                             |
| Shock resistance                            | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                            | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance                        | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Contact blocks configuration                | Max no. 8 blocks (4+4)                           |
| Material                                    | PA Polyamide                                     |
| Cap or bellow material                      | Silicon rubber                                   |
| Button/mushroom material (illuminated type) | PC Polycarbonate                                 |
| Locking ring material                       | Zamak zinc alloy                                 |
| Fixing diameter                             | 22.5mm - Thickness 1÷6mm                         |
| Tightening torque                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Actuation type                              | Spring return                                    |
| Protection against electric shock           | Class II (IEC-EN61140)                           |
| Illuminated version                         | Use Ba9S bulbs with 24mm height max.             |

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Disegni tecnici

