

Scheda Dati

020PPLIBPP

Lichtdrukknop met bescherming, stabiel, wit, Bescherming kleurloos vergrendeling, veer sluiting



Caratteristiche

Bereik	Lichtdrukknoppen Ø 22
Componente	Drukknoppen met bescherming, afsluitbare bescherming
Rubriek	020PPLIBPP
Omschrijving	Lichtdrukknop met bescherming, stabiel, wit, Bescherming kleurloos vergrendeling, veer sluiting
Kleur	Bianco
Peso	28,0
Tariffa doganale	85365080
GTIN	8052878068783

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	500.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Material	PA Polyamide
Button/mushroom material (illuminated type)	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Push-Push (maintained position)
Protection against electric shock	Class II (IEC-EN61140)

Illuminated version

Use Ba9S bulbs with 24mm height max.

Warranty period

18 months

Disegni tecnici

