

Fiche technique

020PPTAFLGW

Bouton-poussoir coup de poing Ø 38, lumineux, stable, jaune



Caractéristiques

| | |
|-------------------------------------|---|
| Portée | B.P. coup de poing lumineux Ø 22 - collerette métallique |
| Composant | Bouton coup de poing Ø 38 |
| Code | 020PPTAFLGW |
| Désignation des marchandises | Bouton-poussoir coup de poing Ø 38, lumineux, stable, jaune |
| Couleur | Giallo |
| Poids | 36,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878007744 |

Données techniques

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 3.000.000 Operations |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 6 blocks (3+3) |
| Button/mushroom material (illuminated type) | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Actuation type | Push-Push (maintained position) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Dessins techniques

