

## Datenblatt

020PPTAFVW

Pilztaster Ø 40, permanent, grün



## Merkmale

|                        |  |
|------------------------|--|
| <b>Baureihe</b>        | Unbeleuchtete Pilztaster Ø 22 - Metallschutz |
| <b>Komponenten</b>     | Pilztaster Ø 40                              |
| <b>Artikel-Nr.</b>     | 020PPTAFVW                                   |
| <b>Beschreibung</b>    | Pilztaster Ø 40, permanent, grün             |
| <b>Farbe</b>           | Verde  |
| <b>Gewicht - gr</b>    | 32,0   |
| <b>Zolltarifnummer</b> | 85365080                                     |
| <b>GTIN</b>            | 8052878007805                                |

## Technische Daten

|  |  |
|--|--|
| <b>Approvals</b>                                   | CE   |
| <b>Compliance with standards</b>                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Compliance with standards</b>                   | UNI CEI EN 45545-2                               |
| <b>Operating temperatures</b>                      | -25° ÷ +65°C                                     |
| <b>Environmental operating values</b>              | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| <b>Protection degree</b>                           | IP65 (IEC-EN60529)                               |
| <b>Protection against impact</b>                   | IK03 (IEC-EN62262)                               |
| <b>Mechanical durability</b>                       | 3.000.000 Operations                             |
| <b>Shock resistance</b>                            | 50g duration=11ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>                        | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Contact blocks configuration</b>                | Max no. 6 blocks (3+3)                           |
| <b>Button/mushroom material (illuminated type)</b> | PC Polycarbonate                                 |
| <b>External bezel material</b>                     | Chromed zinc alloy                               |
| <b>Locking ring material</b>                       | Zamak zinc alloy                                 |
| <b>Fixing diameter</b>                             | 22.5mm - Thickness 1÷6mm                         |
| <b>Tightening torque</b>                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| <b>Actuation type</b>                              | Push-Push (maintained position)                  |
| <b>Protection against electric shock</b>           | Class II (IEC-EN61140)                           |
| <b>Warranty period</b>                             | 18 months  |

## Technische Zeichnungen

