

## Scheda Dati

020PPTASRW  
Botão saliente, estável, vermelho



## Caratteristiche

|                  |                                           |
|------------------|-------------------------------------------|
| Gama             | Botões não luminosos Ø 22 - anel em metal |
| Componente       | Botões salientes                          |
| Código           | 020PPTASRW                                |
| Descrição        | Botão saliente, estável, vermelho         |
| Cor              | Rosso                                     |
| Peso             | 33,0                                      |
| Tariffa doganale | 85365080                                  |
| GTIN             | 8052878008253                             |

## Dati tecnici

|                                             |                                                  |
|---------------------------------------------|--------------------------------------------------|
| Approvals                                   | CE                                               |
| Compliance with standards                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards                   | UNI CEI EN 45545-2                               |
| Operating temperatures                      | -25° ÷ +65°C                                     |
| Environmental operating values              | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| Protection degree                           | IP65 (IEC-EN60529)                               |
| Protection against impact                   | IK03 (IEC-EN62262)                               |
| Mechanical durability                       | 3.000.000 Operations                             |
| Shock resistance                            | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance                        | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Contact blocks configuration                | Max no. 6 blocks (3+3)                           |
| Button/mushroom material (illuminated type) | PC Polycarbonate                                 |
| External bezel material                     | Chromed zinc alloy                               |
| Locking ring material                       | Zamak zinc alloy                                 |
| Fixing diameter                             | 22.5mm - Thickness 1÷6mm                         |
| Tightening torque                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Actuation type                              | Push-Push (maintained position)                  |
| Protection against electric shock           | Class II (IEC-EN61140)                           |
| Warranty period                             | 18 months                                        |

## Disegni tecnici

