

## Hoja de datos

020PTAASRKP02S

Botón parada emergencia rojo 52 mm con giro aro bloqueable, 2 NC automonitoreo



## Características

Rango	Pulsadores emergencia no luminosos Ø 22-protección a candado
Componente	Pulsadores fungiformes Ø 52, protección para candado
Código	020PTAASRKP02S
Descripción	Botón parada emergencia rojo 52 mm con giro aro bloqueable, 2 NC automonitoreo
Color	Rosso
Peso	74,0
Arancel aduanero	85365080
GTIN	8052878069292

## Datos técnicos

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	500.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Material	PA Polyamide
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Trigger action and mechanical latching
Protection against electric shock	Class II (IEC-EN61140)
Yellow padlockable guard	Aluminium painted RAL 1023

---

<b>Padlock with long shackle</b>	Shackle lenght 63mm - 5mm diameter (Not included)
<b>Contacts block</b>	Self-monitoring 2NC block - 020GE02S included
<b>Contacts block characteristics</b>	See item 020GE02S - 2NC self-monitoring
<b>Warranty period</b>	18 months

---

# Dibujos técnicos

