

Scheda Dati

020PTARP02S

Kupukantainen painike Ø 32, avaus kiertämällä, punainen, 2 N.C., itse valvova, holkki lukolla



Caratteristiche

|                  |                                                                                               |
|------------------|-----------------------------------------------------------------------------------------------|
| Range            | Valaamattomat hätäpysäytyspainikkeet Ø 22 - holkki lukolla                                    |
| Componente       | Kupukantaiset painikkeet Ø 32, lukittava kaulus                                               |
| Code             | 020PTARP02S                                                                                   |
| Kuvaus           | Kupukantainen painike Ø 32, avaus kiertämällä, punainen, 2 N.C., itse valvova, holkki lukolla |
| Väriä            | Rosso                                                                                         |
| Peso             | 74,0                                                                                          |
| Tariffa doganale | 85365080                                                                                      |
| GT               | 8052878069278                                                                                 |

Dati tecnici

|                                   |                                                   |
|-----------------------------------|---------------------------------------------------|
| Approvals                         | CE                                                |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2  |
| Compliance with standards         | UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5 |
| Compliance with standards         | UNI CEI EN 45545-2, CEI EN 61373                  |
| Operating temperatures            | -40° ÷ +70°C                                      |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)                         |
| Protection against impact         | IK03 (IEC-EN62262)                                |
| Mechanical durability             | 500.000 Operations                                |
| Shock resistance                  | 30g duration=18ms (EN-IEC 60068-2-27)             |
| Shock resistance                  | 50g duration=11ms (EN-IEC 60068-2-27)             |
| Vibration resistance              | 5g f= 2...500Hz (EN-IEC 60068-2-6)                |
| Contact blocks configuration      | Max no. 4 blocks (2+2)                            |
| Material                          | PA Polyamide                                      |
| Locking ring material             | Zamak zinc alloy                                  |
| Fixing diameter                   | 22.5mm - Thickness 1÷6mm                          |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                       |
| Actuation type                    | Trigger action and mechanical latching            |
| Protection against electric shock | Class II (IEC-EN61140)                            |
| Yellow padlockable guard          | Aluminium painted RAL 1023                        |

|                                       |                                                   |
|---------------------------------------|---------------------------------------------------|
| <b>Padlock with long shackle</b>      | Shackle lenght 63mm - 5mm diameter (Not included) |
| <b>Contacts block</b>                 | Self-monitoring 2NC block - 020GE02S included     |
| <b>Contacts block characteristics</b> | See item 020GE02S - 2NC self-monitoring           |
| <b>Warranty period</b>                | 18 months                                         |

Disegni tecnici

