

## Scheda Dati

020PTF9PTN

Pulsador fungiforme esférico Ø 90, desenganche tracción, negro



## Caratteristiche

|                         |  |
|-------------------------|--|
| <b>Rango</b>            | Pulsadores de emergencia no luminosos Ø 22                     |
| <b>Componente</b>       | Pulsadores fungiforme esféricos Ø 90, desenganche tracción     |
| <b>Código</b>           | 020PTF9PTN   |
| <b>Descripción</b>      | Pulsador fungiforme esférico Ø 90, desenganche tracción, negro |
| <b>Color</b>            | Nero   |
| <b>Peso</b>             | 55,0   |
| <b>Tariffa doganale</b> | 85365080   |
| <b>GTIN</b>             | 8052878013233  |

## Dati tecnici

|  |   |
|--|---|
| <b>Approvals</b>                         | CE, UL, CSA   |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2    |
| <b>Compliance with standards</b>         | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2, CEI EN 61373                    |
| <b>Operating temperatures</b>            | -40° ÷ +70°C  |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)        |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                           |
| <b>Protection against impact</b>         | IK03 (IEC-EN62262)                                  |
| <b>Mechanical durability</b>             | 500.000 Operations                                  |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)               |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)               |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)                  |
| <b>Contact blocks configuration</b>      | Max no. 4 blocks (2+2)                              |
| <b>Material</b>                          | PA Polyamide  |
| <b>Locking ring material</b>             | Zamak zinc alloy                                    |
| <b>Fixing diameter</b>                   | 22.5mm - Thickness 1÷6mm                            |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                         |
| <b>Actuation type</b>                    | Trigger action and mechanical latching              |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                              |
| <b>Warranty period</b>                   | 18 months   |

# Disegni tecnici

