

Fiche technique

020PTFAG

Bouton d'arrêt d'urgence champignon jaune 40 mm à déverrouillage par rotation



Caractéristiques

Portée	Boutons-poussoirs d'arrêt d'urgence non-lumineux Ø 22
Composant	Bouton coup de poing Ø 40, déverrouillage rotation
Code	020PTFAG
Désignation des marchandises	Bouton d'arrêt d'urgence champignon jaune 40 mm à déverrouillage par rotation
Couleur	Giallo
Poids	36,0
Tarif douanier	85365080
GTIN	8052878065201

Données techniques

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	500.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Material	PA Polyamide
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Trigger action and mechanical latching
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Dessins techniques

