

Datenblatt

020PTFALR4

Beleuchteter Not-Halt Drucktaster rot 40 mm Dreh-Zug Entriegelung mit gelber Scheibe 45 mm



Merkmale

Baureihe	Beleuchtete Not-Halt-Taster Ø 22
Komponenten	Pilztaster Ø 40, Dreh-Zug-Auslösung, gelbe scheinbe
Artikel-Nr.	020PTFALR4
Beschreibung	Beleuchteter Not-Halt Drucktaster rot 40 mm Dreh-Zug Entriegelung mit gelber Scheibe 45 mm
Farbe	Rosso
Gewicht - gr	42,0
Zolltarifnummer	85365080
GTIN	8052878068325

Technische Daten

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	500.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Trigger action and mechanical latching

Actuation type	Push to lock - Pull or rotate to release
Protection against electric shock	Class II (IEC-EN61140)
Illuminated version	Use Ba9S bulbs with 24mm height max.
Warranty period	18 months

Technische Zeichnungen

