

Fiche technique

020PTFALR4

Bouton d'arrêt d'urgence lumineux champignon rouge 40 mm rotation-traction avec disque jaune 45 mm



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Boutons-poussoirs d'arrêt d'urgence lumineux Ø 22 |
| Composant | Bouton coup de poing Ø 40, torsion, disque jaune |
| Code | 020PTFALR4 |
| Désignation des marchandises | Bouton d'arrêt d'urgence lumineux champignon rouge 40 mm rotation-traction avec disque jaune 45 mm |
| Couleur | Rosso |
| Poids | 42,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878068325 |

Données techniques

| | |
|---------------------------------------|---|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 500.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 4 blocks (2+2) |
| Material | PA Polyamide |
| Lens material | PC Polycarbonate |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Actuation type | Trigger action and mechanical latching |

| | |
|--|--|
| Actuation type | Push to lock - Pull or rotate to release |
| Protection against electric shock | Class II (IEC-EN61140) |
| Illuminated version | Use Ba9S bulbs with 24mm height max. |
| Warranty period | 18 months |

Dessins techniques

