

## Datenblatt

### 020PTFALR6

Beleuchteter Not-Halt Drucktaster rot 40 mm Dreh-Zug Entriegelung mit gelber Scheibe 60 mm



## Merkmale

|                        |  |
|------------------------|--|
| <b>Baureihe</b>        | Beleuchtete Not-Halt-Taster Ø 22   |
| <b>Komponenten</b>     | Pilztaster Ø 40, Dreh-Zug-Auslösung, gelbe scheinbe  |
| <b>Artikel-Nr.</b>     | 020PTFALR6   |
| <b>Beschreibung</b>    | Beleuchteter Not-Halt Drucktaster rot 40 mm Dreh-Zug Entriegelung mit gelber Scheibe 60 mm |
| <b>Farbe</b>           | Rosso  |
| <b>Gewicht - gr</b>    | 44,0   |
| <b>Zolltarifnummer</b> | 85365080   |
| <b>GTIN</b>            | 8052878068332  |

## Technische Daten

|                                       |   |
|---------------------------------------|---|
| <b>Approvals</b>                      | CE  |
| <b>Compliance with standards</b>      | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2    |
| <b>Compliance with standards</b>      | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| <b>Compliance with standards</b>      | UNI CEI EN 45545-2, CEI EN 61373                    |
| <b>Operating temperatures</b>         | -40° ÷ +70°C  |
| <b>Environmental operating values</b> | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)        |
| <b>Protection degree</b>              | IP66 - IP69 (IEC-EN60529)                           |
| <b>Protection against impact</b>      | IK03 (IEC-EN62262)                                  |
| <b>Mechanical durability</b>          | 500.000 Operations                                  |
| <b>Shock resistance</b>               | 30g duration=18ms (EN-IEC 60068-2-27)               |
| <b>Shock resistance</b>               | 50g duration=11ms (EN-IEC 60068-2-27)               |
| <b>Vibration resistance</b>           | 5g f= 2...500Hz (EN-IEC 60068-2-6)                  |
| <b>Contact blocks configuration</b>   | Max no. 4 blocks (2+2)                              |
| <b>Material</b>                       | PA Polyamide  |
| <b>Lens material</b>                  | PC Polycarbonate                                    |
| <b>Locking ring material</b>          | Zamak zinc alloy                                    |
| <b>Fixing diameter</b>                | 22.5mm - Thickness 1÷6mm                            |
| <b>Tightening torque</b>              | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                         |
| <b>Actuation type</b>                 | Trigger action and mechanical latching              |

---

|  |  |
|--|--|
| <b>Actuation type</b>                    | Push to lock - Pull or rotate to release |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                   |
| <b>Illuminated version</b>               | Use Ba9S bulbs with 24mm height max.     |
| <b>Warranty period</b>                   | 18 months                                |

---

## Technische Zeichnungen

