

## Datenblatt

020PTFAR

Not-Halt Drucktaster rot 40 mm mit Drehentriegelung



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Not-Halt-Taster unbeleuchtet Ø 22                   |
| <b>Komponenten</b>     | Pilztaster Ø 40, Drehentriegelung                   |
| <b>Artikel-Nr.</b>     | 020PTFAR  |
| <b>Beschreibung</b>    | Not-Halt Drucktaster rot 40 mm mit Drehentriegelung |
| <b>Farbe</b>           | Rosso   |
| <b>Gewicht - gr</b>    | 36,0  |
| <b>Zolltarifnummer</b> | 85365080  |
| <b>GTIN</b>            | 8052878013264                                       |

## Technische Daten

|  |   |
|--|---|
| <b>Approvals</b>                         | CE, UL, CSA   |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2    |
| <b>Compliance with standards</b>         | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2, CEI EN 61373                    |
| <b>Operating temperatures</b>            | -40° ÷ +70°C  |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)        |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                           |
| <b>Protection against impact</b>         | IK03 (IEC-EN62262)                                  |
| <b>Mechanical durability</b>             | 500.000 Operations                                  |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)               |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)               |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)                  |
| <b>Contact blocks configuration</b>      | Max no. 4 blocks (2+2)                              |
| <b>Material</b>                          | PA Polyamide  |
| <b>Locking ring material</b>             | Zamak zinc alloy                                    |
| <b>Fixing diameter</b>                   | 22.5mm - Thickness 1÷6mm                            |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                         |
| <b>Actuation type</b>                    | Trigger action and mechanical latching              |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                              |
| <b>Warranty period</b>                   | 18 months   |

# Technische Zeichnungen

