

## Scheda Dati

020PTFASRVP02

Pulsador fungiforme Ø 42, desenganche a rotación, rojo, 2 N.C., protección telescópica a candado, metal



## Caratteristiche

<b>Rango</b>	Pulsadores emergencia no luminosos Ø 22-protección a candado
<b>Componente</b>	Pulsadores fungiformes Ø 42, protección para candado
<b>Código</b>	020PTFASRVP02
<b>Descripción</b>	Pulsador fungiforme Ø 42, desenganche a rotación, rojo, 2 N.C., protección telescópica a candado, metal
<b>Color</b>	Rosso
<b>Peso</b>	106,0
<b>Tariffa doganale</b>	85365080
<b>GTIN</b>	8052878067571

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Compliance with standards</b>	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
<b>Compliance with standards</b>	UNI CEI EN 45545-2, CEI EN 61373
<b>Operating temperatures</b>	-40° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK03 (IEC-EN62262)
<b>Mechanical durability</b>	500.000 Operations
<b>Shock resistance</b>	30g duration=18ms (EN-IEC 60068-2-27)
<b>Shock resistance</b>	50g duration=11ms (EN-IEC 60068-2-27)
<b>Vibration resistance</b>	5g f= 2...500Hz (EN-IEC 60068-2-6)
<b>Contact blocks configuration</b>	Max no. 4 blocks (2+2)
<b>Material</b>	PA Polyamide
<b>Locking ring material</b>	Zamak zinc alloy
<b>Fixing diameter</b>	22.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Actuation type</b>	Trigger action and mechanical latching
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Contact block</b>	Included

---

<b>Yellow padlockable guard</b>	Aluminium painted RAL 1023
<b>Padlock with long shackle</b>	Shackle lenght 63mm - 5mm diameter (Not included)
<b>Contacts block characteristics</b>	See item 020GE02 - 2NC contacts block
<b>Warranty period</b>	18 months

---

# Disegni tecnici

