

Hoja de datos

020PTFN

Pulsador fungiforme Ø 40, negro



Características

| | |
|------------------|--|
| Rango | Pulsadores fungiformes no luminosos Ø 22 |
| Componente | Pulsadores fungiformes Ø 40 |
| Código | 020PTFN |
| Descripción | Pulsador fungiforme Ø 40, negro |
| Color | Nero |
| Peso | 36,0 |
| Arancel aduanero | 85365080 |
| GTIN | 8052878013370 |

Datos técnicos

| | |
|-----------------------------------|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 3.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 6 blocks (3+3) |
| Material | PA Polyamide |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Actuation type | Spring return |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Dibujos técnicos

