

## Scheda Dati

020PTHCRW

Kupukantainen painike Ø 40, avaus avaimella K37, punainen, metalli



## Caratteristiche

|                  |  |
|------------------|--|
| Range            | Hätäpainikkeet Ø 22 - metallirengas                                |
| Componente       | Kupukantaiset painikkeet Ø 40, avaus avaimella                     |
| Code             | 020PTHCRW  |
| Kuvaus           | Kupukantainen painike Ø 40, avaus avaimella K37, punainen, metalli |
| Väriä            | Rosso  |
| Peso             | 94,0   |
| Tariffa doganale | 85365080   |
| GT               | 8052878013493  |

## Dati tecnici

|                                   |   |
|-----------------------------------|---|
| Approvals                         | CE  |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2    |
| Compliance with standards         | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| Compliance with standards         | UNI CEI EN 45545-2                                  |
| Operating temperatures            | -25° ÷ +65°C  |
| Environmental operating values    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)        |
| Protection degree                 | IP65 (IEC-EN60529)                                  |
| Protection against impact         | IK03 (IEC-EN62262)                                  |
| Mechanical durability             | 500.000 Operations                                  |
| Shock resistance                  | 30g duration=18ms (EN-IEC 60068-2-27)               |
| Shock resistance                  | 50g duration=11ms (EN-IEC 60068-2-27)               |
| Vibration resistance              | 5g f= 2...500Hz (EN-IEC 60068-2-6)                  |
| Contact blocks configuration      | Max no. 4 blocks (2+2)                              |
| Material                          | PA Polyamide  |
| External bezel material           | Chromed zinc alloy                                  |
| Locking ring material             | Zamak zinc alloy                                    |
| Fixing diameter                   | 22.5mm - Thickness 1÷6mm                            |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                         |
| Actuation type                    | Trigger action and mechanical latching              |
| Protection against electric shock | Class II (IEC-EN61140)                              |

---

**Warranty period**

18 months

---

## Disegni tecnici

