

## Scheda Dati

020PTHCRW

Bouton-poussoir coup de poing Ø 40, déverrouillage par clé K37, rouge, métal



## Caratteristiche

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Boutons-poussoirs d'arrêt d'urgence Ø 22 - collerette métal.                 |
| <b>Componente</b>                   | Bouton coup de poing Ø 40, déverrouillage par clé                            |
| <b>Code</b>                         | 020PTHCRW  |
| <b>Désignation des marchandises</b> | Bouton-poussoir coup de poing Ø 40, déverrouillage par clé K37, rouge, métal |
| <b>Couleur</b>                      | Rosso  |
| <b>Peso</b>                         | 94,0   |
| <b>Tariffa doganale</b>             | 85365080   |
| <b>GTIN</b>                         | 8052878013493  |

## Dati tecnici

|  |   |
|--|---|
| <b>Approvals</b>                         | CE  |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2    |
| <b>Compliance with standards</b>         | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2                                  |
| <b>Operating temperatures</b>            | -25° ÷ +65°C  |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)        |
| <b>Protection degree</b>                 | IP65 (IEC-EN60529)                                  |
| <b>Protection against impact</b>         | IK03 (IEC-EN62262)                                  |
| <b>Mechanical durability</b>             | 500.000 Operations                                  |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)               |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)               |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)                  |
| <b>Contact blocks configuration</b>      | Max no. 4 blocks (2+2)                              |
| <b>Material</b>                          | PA Polyamide  |
| <b>External bezel material</b>           | Chromed zinc alloy                                  |
| <b>Locking ring material</b>             | Zamak zinc alloy                                    |
| <b>Fixing diameter</b>                   | 22.5mm - Thickness 1÷6mm                            |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                         |
| <b>Actuation type</b>                    | Trigger action and mechanical latching              |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                              |

---

**Warranty period**

18 months

---

## Disegni tecnici

