

Datablad

020PTHCRW

Noodstop drukknoop rood 40 mm met sleutelontgrendeling K37 en metalen ring



Kenmerken

Bereik	Noodstopknoppen Ø 22 - metalen ringmoer
Component	Noodstopknoppen Ø 40, sleutel ontgrendeling
Rubriek	020PTHCRW
Omschrijving	Noodstop drukknoop rood 40 mm met sleutelontgrendeling K37 en metalen ring
Kleur	Rosso
Gewicht	94,0
Douanetarief	85365080
GTIN	8052878013493

Technische gegevens

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	UNI CEI EN 45545-2
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	500.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Material	PA Polyamide
External bezel material	Chromed zinc alloy
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Trigger action and mechanical latching
Protection against electric shock	Class II (IEC-EN61140)

Warranty period

18 months

Technische tekeningen

