

Datasheet

020PUSB

USB socket 3.0 type A-A (female-female)



Features

| | |
|-----------------------|---|
| Range | USB sockets Ø 22 |
| components | USB socket 3.0 female-female |
| Code | 020PUSB |
| Description | USB socket 3.0 type A-A (female-female) |
| Colour | Nero |
| Weight - gr | 24.0 |
| Customs Tariff | 85366990 |
| GTIN | 8052878013967 |

Datasheet

| | |
|---------------------------------------|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2 |
| Compliance with standards | USB 3.0 type A |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | all climates +40°C and 92% RH |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Material | PA Polyamide |
| Locking ring material | PA Polyamide |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in) |
| USB model | USB 3.0 9 pin, type A-A (female-female) |
| USB model | USB 3.0 24 pin, type C-A (female-female) |
| Protection degree | IP20 / IP66 with cap closed (IEC-EN60529) |
| Nominal voltage | 5V AC/DC - 30V max |
| Baud rate | 5Gbit/sec |
| Insulation resistance | >100MΩ |
| Contact resistance | <30mΩ |
| Power on | LED presence checking the right connection |
| LED durability | >50.000 h |

| | |
|----------------------------|-------------------------|
| Mechanical lifespan | >15000 insertion cycles |
| Warranty period | 18 months |

Technical drawings

