# Fiche technique

020PUSB
Prise USB 3.0 mod. A-A (femelle-femelle)





## Caractéristiques

| | |
|---|---|
| **Portée** | Prises USB Ø 22 |
| **Composant** | Prise USB 3.0 femelle-femelle |
| **Code** | 020PUSB |
| **Désignation des marchandises** | Prise USB 3.0 mod. A-A (femelle-femelle) |
| **Couleur** | Nero |
| **Poids** | 24,0 |
| **Tarif douanier** | 85366990 |
| **GTIN** | 8052878013967 |

## Données techniques

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| **Compliance with standards** | UNI CEI EN 45545-2 |
| **Compliance with standards** | USB 3.0 type A |
| **Operating temperatures** | -40° ÷ +70°C |
| **Environmental operating values** | all climates +40°C and 92% RH |
| **Shock resistance** | 30g duration=18ms (EN-IEC 60068-2-27) |
| **Vibration resistance** | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| **Material** | PA Polyamide |
| **Locking ring material** | PA Polyamide |
| **Fixing diameter** | 22.5mm - Thickness 1÷6mm |
| **Tightening torque** | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in) |
| **USB model** | USB 3.0 9 pin, type A-A (female-female) |
| **USB model** | USB 3.0 24 pin, type C-A (female-female) |
| **Protection degree** | IP20 / IP66 with cap closed (IEC-EN60529) |
| **Nominal voltage** | 5V AC/DC - 30V max |
| **Baud rate** | 5Gbit/sec |
| **Insulation resistance** | >100MOhm |
| **Contact resistance** | <30mOhm |
| **Power on** | LED presence checking the right connection |
| **LED durability** | >50.000 h |

| | |
|---|---|
| **Mechanical lifespan** | >15000 insertion cycles |
| **Warranty period** | 18 months |

## Dessins techniques

