

## Scheda Dati

020PUSB

Presse USB 3.0 tipo A-A (femmina-femmina)



## Caratteristiche

<b>Gamma</b>	Presse USB Ø 22
<b>Componente</b>	Presse USB 3.0 femmina-femmina
<b>Codice</b>	020PUSB
<b>Descrizione</b>	Presse USB 3.0 tipo A-A (femmina-femmina)
<b>Colore</b>	Nero
<b>Peso</b>	24,0
<b>Tariffa doganale</b>	85366990
<b>GTIN</b>	8052878013967

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Compliance with standards</b>	UNI CEI EN 45545-2
<b>Compliance with standards</b>	USB 3.0 type A
<b>Operating temperatures</b>	-40° ÷ +70°C
<b>Environmental operating values</b>	all climates +40°C and 92% RH
<b>Shock resistance</b>	30g duration=18ms (EN-IEC 60068-2-27)
<b>Vibration resistance</b>	5g f= 2...500Hz (EN-IEC 60068-2-6)
<b>Material</b>	PA Polyamide
<b>Locking ring material</b>	PA Polyamide
<b>Fixing diameter</b>	22.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
<b>USB model</b>	USB 3.0 9 pin, type A-A (female-female)
<b>USB model</b>	USB 3.0 24 pin, type C-A (female-female)
<b>Protection degree</b>	IP20 / IP66 with cap closed (IEC-EN60529)
<b>Nominal voltage</b>	5V AC/DC - 30V max
<b>Baud rate</b>	5Gbit/sec
<b>Insulation resistance</b>	>100MΩ
<b>Contact resistance</b>	<30mΩ
<b>Power on</b>	LED presence checking the right connection
<b>LED durability</b>	>50.000 h

---

<b>Mechanical lifespan</b>	>15000 insertion cycles
<b>Warranty period</b>	18 months

---

## Disegni tecnici

