

Scheda Dati

020PUSB

USB-aansluiting 3.0 type A-A (vrouw-vrouw)



Caratteristiche

Bereik	USB-aansluitingen Ø 22
Componente	USB-aansluiting 3.0 vrouw-vrouw
Rubriek	020PUSB
Omschrijving	USB-aansluiting 3.0 type A-A (vrouw-vrouw)
Kleur	Nero
Peso	24,0
Tariffa doganale	85366990
GTIN	8052878013967

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2
Compliance with standards	USB 3.0 type A
Operating temperatures	-40° ÷ +70°C
Environmental operating values	all climates +40°C and 92% RH
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Material	PA Polyamide
Locking ring material	PA Polyamide
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
USB model	USB 3.0 9 pin, type A-A (female-female)
USB model	USB 3.0 24 pin, type C-A (female-female)
Protection degree	IP20 / IP66 with cap closed (IEC-EN60529)
Nominal voltage	5V AC/DC - 30V max
Baud rate	5Gbit/sec
Insulation resistance	>100MΩ
Contact resistance	<30mΩ
Power on	LED presence checking the right connection
LED durability	>50.000 h

Mechanical lifespan	>15000 insertion cycles
Warranty period	18 months

Disegni tecnici

