

## Datenblatt

020PUSBC

USB-Buchse 3.0 Typ C-A (weiblich-weiblich)



## Merkmale

<b>Baureihe</b>	USB-Buchsen Ø 22
<b>Komponenten</b>	USB-Buchse 3.0 weiblich-weiblich
<b>Artikel-Nr.</b>	020PUSBC
<b>Beschreibung</b>	USB-Buchse 3.0 Typ C-A (weiblich-weiblich)
<b>Farbe</b>	Nero
<b>Gewicht - gr</b>	22,0
<b>Zolltarifnummer</b>	85366990
<b>GTIN</b>	8052878068929

## Technische Daten

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Compliance with standards</b>	UNI CEI EN 45545-2
<b>Compliance with standards</b>	USB 3.0 type A
<b>Operating temperatures</b>	-40° ÷ +70°C
<b>Environmental operating values</b>	all climates +40°C and 92% RH
<b>Shock resistance</b>	30g duration=18ms (EN-IEC 60068-2-27)
<b>Vibration resistance</b>	5g f= 2...500Hz (EN-IEC 60068-2-6)
<b>Material</b>	PA Polyamide
<b>Locking ring material</b>	PA Polyamide
<b>Fixing diameter</b>	22.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
<b>USB model</b>	USB 3.0 9 pin, type A-A (female-female)
<b>USB model</b>	USB 3.0 24 pin, type C-A (female-female)
<b>Protection degree</b>	IP20 / IP66 with cap closed (IEC-EN60529)
<b>Nominal voltage</b>	5V AC/DC - 30V max
<b>Baud rate</b>	5Gbit/sec
<b>Insulation resistance</b>	>100MΩ
<b>Contact resistance</b>	<30mΩ
<b>Power on</b>	LED presence checking the right connection
<b>LED durability</b>	>50.000 h

---

<b>Mechanical lifespan</b>	>15000 insertion cycles
<b>Warranty period</b>	18 months

---

# Technische Zeichnungen

