

Datasheet

020PUSBC

USB socket 3.0 type C-A (female-female)



Features

Range	USB sockets Ø 22
components	USB socket 3.0 female-female
Code	020PUSBC
Description	USB socket 3.0 type C-A (female-female)
Colour	Nero
Weight - gr	22.0
Customs Tariff	85366990
GTIN	8052878068929

Datasheet

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2
Compliance with standards	USB 3.0 type A
Operating temperatures	-40° ÷ +70°C
Environmental operating values	all climates +40°C and 92% RH
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Material	PA Polyamide
Locking ring material	PA Polyamide
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
USB model	USB 3.0 9 pin, type A-A (female-female)
USB model	USB 3.0 24 pin, type C-A (female-female)
Protection degree	IP20 / IP66 with cap closed (IEC-EN60529)
Nominal voltage	5V AC/DC - 30V max
Baud rate	5Gbit/sec
Insulation resistance	>100MΩ
Contact resistance	<30mΩ
Power on	LED presence checking the right connection
LED durability	>50.000 h

Mechanical lifespan	>15000 insertion cycles
Warranty period	18 months

Technical drawings

