

## Fiche technique

020PUSBC

Prise USB 3.0 mod. C-A (femelle-femelle)



## Caractéristiques

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Prises USB Ø 22                          |
| <b>Composant</b>                    | Prise USB 3.0 femelle-femelle            |
| <b>Code</b>                         | 020PUSBC                                 |
| <b>Désignation des marchandises</b> | Prise USB 3.0 mod. C-A (femelle-femelle) |
| <b>Couleur</b>                      | Nero                                     |
| <b>Poids</b>                        | 22,0                                     |
| <b>Tarif douanier</b>               | 85366990                                 |
| <b>GTIN</b>                         | 8052878068929                            |

## Données techniques

|                                       |  |
|---------------------------------------|--|
| <b>Approvals</b>                      | CE   |
| <b>Compliance with standards</b>      | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Compliance with standards</b>      | UNI CEI EN 45545-2                               |
| <b>Compliance with standards</b>      | USB 3.0 type A                                   |
| <b>Operating temperatures</b>         | -40° ÷ +70°C                                     |
| <b>Environmental operating values</b> | all climates +40°C and 92% RH                    |
| <b>Shock resistance</b>               | 30g duration=18ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>           | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Material</b>                       | PA Polyamide                                     |
| <b>Locking ring material</b>          | PA Polyamide                                     |
| <b>Fixing diameter</b>                | 22.5mm - Thickness 1÷6mm                         |
| <b>Tightening torque</b>              | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                       |
| <b>USB model</b>                      | USB 3.0 9 pin, type A-A (female-female)          |
| <b>USB model</b>                      | USB 3.0 24 pin, type C-A (female-female)         |
| <b>Protection degree</b>              | IP20 / IP66 with cap closed (IEC-EN60529)        |
| <b>Nominal voltage</b>                | 5V AC/DC - 30V max                               |
| <b>Baud rate</b>                      | 5Gbit/sec  |
| <b>Insulation resistance</b>          | >100MΩ   |
| <b>Contact resistance</b>             | <30mΩ  |
| <b>Power on</b>                       | LED presence checking the right connection       |
| <b>LED durability</b>                 | >50.000 h  |

---

|                            |                         |
|----------------------------|-------------------------|
| <b>Mechanical lifespan</b> | >15000 insertion cycles |
| <b>Warranty period</b>     | 18 months               |

---

## Dessins techniques

