

Datenblatt

020RTAIBL Reset-Drucktaster, blau



Merkmale

| | |
|------------------------|---------------------------|
| Baureihe | Unbeleuchtete Taster Ø 22 |
| Komponenten | Reset-Drucktaster |
| Artikel-Nr. | 020RTAIBL |
| Beschreibung | Reset-Drucktaster, blau |
| Farbe | Blu |
| Gewicht - gr | 31,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878014216 |

Technische Daten

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 3.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Material | PA Polyamide |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Actuation type | Spring return |
| Protection against electric shock | Class II (IEC-EN61140) |
| Adjustable rod material | Zinc plated steel + insulated actuator |
| Warranty period | 18 months |

Technische Zeichnungen

