


## Scheda Dati

020RTAIR

Botão de rearme , vermelho



## Caratteristiche

|                  |                            |
|------------------|----------------------------|
| Gama             | Botões não luminosos Ø 22  |
| Componente       | Botões de rearme           |
| Código           | 020RTAIR                   |
| Descrição        | Botão de rearme , vermelho |
| Cor              | Rosso                      |
| Peso             | 33,0                       |
| Tariffa doganale | 85365080                   |
| GTIN             | 8052878014261              |

## Dati tecnici

|                                   |  |
|-----------------------------------|--|
| Approvals                         | CE   |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures            | -25° ÷ +65°C                                     |
| Protection degree                 | IP65 (IEC-EN60529)                               |
| Protection against impact         | IK03 (IEC-EN62262)                               |
| Mechanical durability             | 3.000.000 Operations                             |
| Shock resistance                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Material                          | PA Polyamide                                     |
| Locking ring material             | Zamak zinc alloy                                 |
| Fixing diameter                   | 22.5mm - Thickness 1÷6mm                         |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Actuation type                    | Spring return                                    |
| Protection against electric shock | Class II (IEC-EN61140)                           |
| Adjustable rod material           | Zinc plated steel + insulated actuator           |
| Warranty period                   | 18 months  |

## Disegni tecnici

