

Scheda Dati

020SA24

Segnalatore acustico, 24 V AC-DC



Caratteristiche

| | |
|-------------------------|----------------------------------|
| Gamma | Segnalatori acustici Ø 22 |
| Componente | Acustico |
| Codice | 020SA24 |
| Descrizione | Segnalatore acustico, 24 V AC-DC |
| Colore | Nero |
| Peso | 20,0 |
| Tariffa doganale | 85318070 |
| GTIN | 8052878014377 |

Dati tecnici

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +50°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP67 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Material | PA Polyamide |
| Lens material | PC Polycarbonate |
| Locking ring material | PA Polyamide |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in) |
| Current consumption | 20mA |
| Sound | 80dB (1m) intermittent single tone |
| Operating Voltage | +/- 20% - (AC models frequency 50÷60Hz) |
| Electrical life | >30.000 hour (continuous work) |
| Brightness (illuminated version) | 60cd/m2 |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Disegni tecnici

