

Scheda Dati

020SA24
Sinalizador acústico, 24 V CA-CC



Caratteristiche

Gama	Sinalizadores acústicos Ø 22
Componente	Sinalizador acústico
Código	020SA24
Descrição	Sinalizador acústico, 24 V CA-CC
Cor	Nero
Peso	20,0
Tariffa doganale	85318070
GTIN	8052878014377

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +50°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP67 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	PA Polyamide
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Current consumption	20mA
Sound	80dB (1m) intermittent single tone
Operating Voltage	+/- 20% - (AC models frequency 50÷60Hz)
Electrical life	>30.000 hour (continuous work)
Brightness (illuminated version)	60cd/m2
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Disegni tecnici

