

## Datenblatt

020SAL13

Lichtsummer, 130 V AC-DC



## Merkmale

<b>Baureihe</b>	Summer Ø 22
<b>Komponenten</b>	Lichtsummer
<b>Artikel-Nr.</b>	020SAL13
<b>Beschreibung</b>	Lichtsummer, 130 V AC-DC
<b>Farbe</b>	Rosso
<b>Gewicht - gr</b>	20,0
<b>Zolltarifnummer</b>	85318070
<b>GTIN</b>	8052878014384

## Technische Daten

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +50°C
<b>Environmental operating values</b>	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
<b>Protection degree</b>	IP67 (IEC-EN60529)
<b>Protection against impact</b>	IK03 (IEC-EN62262)
<b>Material</b>	PA Polyamide
<b>Lens material</b>	PC Polycarbonate
<b>Locking ring material</b>	PA Polyamide
<b>Fixing diameter</b>	22.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
<b>Current consumption</b>	20mA
<b>Sound</b>	80dB (1m) intermittent single tone
<b>Operating Voltage</b>	+/- 20% - (AC models frequency 50÷60Hz)
<b>Electrical life</b>	>30.000 hour (continuous work)
<b>Brightness (illuminated version)</b>	60cd/m2
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Warranty period</b>	18 months

# Technische Zeichnungen

