

Hoja de datos

020SAL22

Señalador acústico y luminoso, 230 V AC



Características

| | |
|------------------|---|
| Rango | Señaladores acústicos Ø 22 |
| Componente | Señalador acústico y luminoso |
| Código | 020SAL22 |
| Descripción | Señalador acústico y luminoso, 230 V AC |
| Color | Rosso |
| Peso | 20,0 |
| Arancel aduanero | 85318070 |
| GTIN | 8052878014391 |

Datos técnicos

| | |
|-----------------------------------|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +50°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP67 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Material | PA Polyamide |
| Lens material | PC Polycarbonate |
| Locking ring material | PA Polyamide |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in) |
| Current consumption | 20mA |
| Sound | 80dB (1m) intermittent single tone |
| Operating Voltage | +/- 20% - (AC models frequency 50÷60Hz) |
| Electrical life | >30.000 hour (continuous work) |
| Brightness (illuminated version) | 60cd/m2 |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Dibujos técnicos

