

## Scheda Dati

020SAL22

Segnalatore acustico e luminoso, 230 V AC



## Caratteristiche

<b>Gamma</b>	Segnalatori acustici Ø 22
<b>Componente</b>	Acustico e luminoso
<b>Codice</b>	020SAL22
<b>Descrizione</b>	Segnalatore acustico e luminoso, 230 V AC
<b>Colore</b>	Rosso
<b>Peso</b>	20,0
<b>Tariffa doganale</b>	85318070
<b>GTIN</b>	8052878014391

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +50°C
<b>Environmental operating values</b>	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
<b>Protection degree</b>	IP67 (IEC-EN60529)
<b>Protection against impact</b>	IK03 (IEC-EN62262)
<b>Material</b>	PA Polyamide
<b>Lens material</b>	PC Polycarbonate
<b>Locking ring material</b>	PA Polyamide
<b>Fixing diameter</b>	22.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
<b>Current consumption</b>	20mA
<b>Sound</b>	80dB (1m) intermittent single tone
<b>Operating Voltage</b>	+/- 20% - (AC models frequency 50÷60Hz)
<b>Electrical life</b>	>30.000 hour (continuous work)
<b>Brightness (illuminated version)</b>	60cd/m2
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Warranty period</b>	18 months

## Disegni tecnici

