

Datenblatt

020SCB2

Schlüssel-Wahlschalter , 2 Positionen, K95-Schlüssel, Cam B, Schlüsselabzug II



Merkmale



Baureihe	Schlüssel-Wahlschalter Ø 22
Komponenten	Schlüssel-Wahlschalter, 2 Positionen
Artikel-Nr.	020SCB2
Beschreibung	Schlüssel-Wahlschalter , 2 Positionen, K95-Schlüssel, Cam B, Schlüsselabzug II
Gewicht - gr	76,0
Zolltarifnummer	85365080
GTIN	8052878014797

Technische Daten

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK06 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 8 blocks (4+4)
Material	PA Polyamide
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Technische Zeichnungen

CAM B



020E01
020E10
020G

